



DAIHATSU
APPLAUSE



APPLAUSE









Specifications

Item		Grade	Li	Xi
Overall length		mm	4350	
Overall width		mm	1660	
Overall height		mm	1385	
Wheelbase		mm	2470	
Track	Front	mm	1425	
	Rear	mm	1415	
Minimum road clearance		mm	140	
Kerb weight	5M/T	kg	975	985
	4A/T	kg	1015	1025
Gross vehicle weight	5M/T	kg	1470	
	4A/T	kg	1515	
Seating capacity			5	
Min. turning radius (tyre)		m	4.8	
Engine type			HD-E, petrol, transverse water-cooled, in-line 4-cylinder, 4-cycle, 16-valve, SOHC	
Total displacement		cc	1590	
Bore x stroke		mm	76.0 x 87.6	
Max. output (EEC)			73 kW/6000 rpm	
Max. torque (EEC)			138 N-m/3600 rpm	
Compression ratio			10.5	
Fuel system			Electronic fuel injection	
Fuel tank capacity		litres	50	
Clutch (manual transmission)			Dry single plate with diaphragm spring and mechanical actuation	
Transmission type	5M/T		Forward 5-speed manual, all-synchromesh	
	4A/T		Forward 4-speed full automatic	
Transmission gear ratio	5M/T		1st-3.090, 2nd-1.750, 3rd-1.250, 4th-0.916, 5th-0.750, Rev-3.142	
	4A/T		1st-3.643, 2nd-2.008, 3rd-1.296, 4th-0.892, Rev-2.977	
Final reduction gear ratio	5M/T		4.266	
	4A/T		2.821	
Steering type			Rack and pinion	
Main brake	Front		Ventilated disc type with booster	
	Rear		Drum type, leading and trailing	
Parking brake			Mechanical type, 2-rear wheel lock	
Suspension	Front		MacPherson strut	
	Rear		MacPherson strut, dual link	
Tyres (standard)			175/70R13	

Note: Daihatsu reserves the right to make changes at any time, without notice, in prices, colours, materials, equipment, specifications and models, and also to discontinue models.
This publication is for international usage, and some specifications and illustrations do not necessarily conform with the models sold in your market.



DAIHATSU MOTOR CO., LTD.

1-1, Daihatsu-cho, Ikeda, Osaka 563, JAPAN

Printed in Japan