

TECHNISCHE GEGEVENS TECHNICAL SPECIFICATIONS NISSAN PRIMERA



LEVERINGSPROGRAMMA / MODEL AVAILABILITY

PRIMERA		4-deurs / 4-door		5-deurs / 5-door		stationwagon	
		5-bak	automaat	5-bak	automaat	5-bak	automaat
		5-speed	automatic	5-speed	automatic	5-speed	automatic
1.6	L (U9)	●					
	LX (U9)	●		●		●	
2.0	LX (U9)	●	●	●	●	●	
	SLX (U9)	●	●	●	●	●	●
	SGX (U9)	●	●	●	●		
	GT (U9)	●		●			
2.0	LX diesel	● (US '87)		● (US '87)		● (US '87)	
	SLX diesel	● (US '87)	●	● (US '87)	●	● (US '87)	


NISSAN

UITVOERINGSSPECIFICATIES / EQUIPMENT SPECIFICATIONS

EXTERIEUR	4/5-deurs / 4/5-door					Wagon		EXTERIOR
	L	LX	SLX	SGX	GT	LX	SLX	
voorrui van gelaagd glas	●	●	●	●	●	●	●	laminated windshield glass
groen getint glas	-	●	●	●	●	●	-	green tinted window glass
brons getint glas	-	-	-	-	-	-	●	bronze tinted window glass
bovenzijde voorruit extra getint	-	-	-	●	-	-	-	dark upper windshield sun shade band
van binnenuit verstelb. halogeen koplampen	●	●	● ¹⁾	●	●	●	●	height adjustable halogen lamps
dubbel halogeen grootlicht	-	-	●	●	●	-	●	dual halogen high beam
achteruitrijlamp(en)	2	2	2	2	2	1	1	reverse lamp(s)
mistachterlicht	●	●	●	●	●	●	●	rear fog lamp
mistlampen vóór	-	-	-	-	●	-	-	front fog lamps
alarmknipperlichtinstallatie	●	●	●	●	●	●	●	hazard warning lights
buitenspiegel links (binnenuit verstelbaar)	●	●	-	-	-	-	-	remote control left door mirror
buitenspiegel rechts (binnenuit verstelbaar)	-	●	-	-	-	-	-	remote control right door mirror
elektrisch bedienbare buitenspiegels	-	-	●	●	●	●	●	electric remote control door mirrors
elektrisch verwarmbare buitenspiegels	-	-	●	●	●	-	●	electric heated door mirrors
ruitewissers 2 snelheden en interval	●	-	-	-	-	-	-	two-speed and intermittent wipers
ruitewissers 2 snelheden en var. interval	-	●	●	●	●	●	●	two-speed and variable intermittent wipers
achterruiwiser met interval en sproeier (5d)	-	●	●	●	●	●	●	rear intermittent wiper and washer (5d)
windvanger linker ruitewisser (2.0 benzine)	-	●	●	●	●	●	●	left side anti-lift wiperblade fin (2.0 petrol)
beschermstrips op de flanken	●	●	●	●	●	●	●	side guard mouldings
antenne	●	●	-	-	-	●	-	antenna
elektrisch bedienbare antenne	-	-	●	●	●	-	●	power antenna
antenne in de achterrui	-	-	-	-	-	-	●	diversity antenna
bumpers in carrosseriekleur	-	-	●	●	●	-	●	body coloured bumpers
grille in carrosseriekleur	●	●	●	●	●	●	●	body coloured front grill
buitenspiegels in carrosseriekleur	-	-	-	●	●	-	-	body coloured door mirrors
voorspoiler	●	●	●	●	●	●	●	front air spoiler
achterspoiler/side skirts in kleur	-	-	-	-	●	-	-	body coloured rr spoiler/side skirts
bumperspoiler v + a in kleur	-	-	-	-	●	-	-	coloured fr + rr bumper spoiler
aerodynamische wieloppen	-	●	●	-	-	●	●	full wheel covers
portierhandels in carrosseriekleur	-	-	-	-	-	●	●	body coloured doorhandles
lichtmetalen velgen	-	-	-	●	●	-	-	alloy wheels
ABS anti-blokkeer remsysteem	-	-	-	-	●	-	-	ABS Anti-lock Braking System
dubbeltonige claxon	●	●	●	●	●	●	●	dual-tone horn

INTERIEUR	4/5-deurs / 4/5-door					Wagon		INTERIOR
	L	LX	SLX	SGX	GT	LX	SLX	
stuurbekrachtiging	-	●	●	●	●	●	●	power steering
in hoogte verstelbaar stuur	-	●	●	●	●	●	●	tilt steering column
2-spaaks stuurwiel zachte rand	●	●	-	-	-	●	-	2-spoke soft padded steering wheel
3-spaaks stuurwiel zachte rand	-	-	●	●	-	-	●	3-spoke soft padded steering wheel
3-spaaks stuurwiel lederen rand	-	-	-	-	●	-	-	3-spoke leather covered steering wheel
stoelbekleding stof	●	-	-	-	-	-	-	woven cloth seat upholstery
stoelbekleding tricot	-	●	-	-	-	●	-	tricot seat upholstery
stoelbekleding van luxe tricot	-	-	●	-	-	-	●	deluxe tricot seat upholstery
stoelbekleding van luxe stof	-	-	-	●	-	-	-	deluxe woven cloth seat upholstery
speciale GT stoelbekleding van luxe stof	-	-	-	-	●	-	-	special GT woven cloth seat upholstery
sportstoelen vóór	-	-	-	-	●	-	-	sport seats front
bestuurdersstoel met hoogte regeling vóór- en achterzijde	-	●	●	●	●	●	●	driver's seat height adjustment front and rear side

¹⁾ niet op diesel automaat / not available on diesel automatic

● = standaard/standard

UITVOERINGSSPECIFICATIES / EQUIPMENT SPECIFICATIONS

INTERIEUR	4-/5-deurs / 4-/5-door					Wagon		INTERIOR
	L	LX	SLX	SGX	GT	LX	SLX	
instelbare lendesteun bestuurderstoel	-	-	●	●	●	-	●	lumbar support drivers seat
traploos verstelbare rugleuningen vóór	●	●	●	●	●	●	●	stepless reclining front seatback
hoogte verstelling hoofdsteunen vóór	●	●	●	●	●	●	●	height adjustable front headrests
kantelbare hoofdsteunen vóór	-	-	-	●	●	-	-	tilt adjustable front headrests
geïntegreerde hoofdsteunen achter	●	-	-	-	-	-	-	integral rear headrests
hoogte verstelling hoofdsteunen achter	-	●	●	●	●	●	●	height adjustable rear headrests
open type hoofdsteunen vóór	-	-	-	-	●	-	-	A-frame front type headrests front
gescheiden opklapbare achterbankzitting (5d)	-	●	●	●	●	●	●	foldable split rear bench (5d)
deelbare achterbankleuning (60/40)	-	●	●	●	●	●	●	split folding rear seatback (60/40)
zithoekverstelling achterbankleuning	-	-	-	-	-	●	●	reclining rear seatback
centrale armsteun achter (4d + wagon)	-	●	●	●	●	●	●	rear centre armrest (4d + wagon)
uitneembare hoedenplank (5d)	-	●	●	●	●	-	-	removable rear parcel shelf
roltype afdekhoes bagageruimte	-	-	-	-	-	●	●	retractable luggage room cover
elektrisch bedienbare zijruiten (v + a)	-	-	●	●	●	-	●	power windows (fr + rr)
centrale portiervergrendeling	-	●	●	●	●	●	●	central doorlock system
portierbekleding afgewerkt met stof	●	●	●	●	●	●	●	cloth door inserts
kaartenvak aan voorportieren	●	●	●	●	●	●	●	front door pockets
tunnelconsole met opbergvak	●	●	●	●	●	●	●	centre console with box
tapijt vloerbedekking	●	●	●	●	●	●	●	carpet floor covering
voetsteun bestuurder	●	●	●	●	●	●	●	driver's footrest
stereo radio/cassettespeler	-	-	-	●	-	-	-	stereo radio/cassetteplayer
2/4 speaker systeem	2	4	4	4	4	4	4	2/4 speaker system
3-punts rol gordels (v + a)	●	●	●	●	●	●	●	3-point ELR fr + rr seatbelts
centrale heupgordel achter	●	●	●	●	●	●	●	centre seatbelt rear
schouderhoogte verstelling gordels vóór	●	●	●	●	●	●	●	front seatbelt shoulder height adjustment
interieurverlichting over 4 portieren	●	●	●	●	●	●	●	roomlamp with 4 door switches
plafondspotjes	-	-	●	●	●	-	●	front spot lights
make-up spiegel in rechter zonneklep	●	●	●	●	●	●	●	vanity mirror in right side sunvisor
afsluitbaar dashboardkastje	●	●	●	●	●	●	●	lockable glove box
verlichting in dashboardkastje	-	●	●	●	●	●	●	glove box with illumination
cassette opbergsysteem	-	-	-	●	-	-	-	cassette box
asbak voor en achter	●	●	●	●	●	●	●	ashtray front and rear
sigarettenaansteker	●	●	●	●	●	●	●	cigarlighter
verlichting asbak en sigarettenaansteker	-	●	●	●	●	●	●	ashtray and cigarlighter illumination
anti-verblindingsbinnenspiegel	●	●	●	●	●	●	●	anti-glare adjustable rear view mirror
tapijt in bagageruimte	●	●	●	●	●	●	●	carpet in luggage room
zijwanden bagageruimte bekleed	●	●	●	●	●	●	●	side trim luggage room
pookknop en handremgreep met leder bekleed	-	-	-	-	●	-	-	shift knob and parking brake lever with leather grip
bagageklep bekleding (std. op 5d/wagon)	-	-	●	●	●	●	●	trunk lid trim (std. on 5d/wagon)
verlichting in bagageruimte	-	●	●	●	●	●	●	luggage area illumination
ontgrendeling koffer- en brandstoftankklep van binnenuit	●	●	●	●	●	●	●	trunk lid and fuel filler lid opener from inside
elektrische achterklep ontgrendeling	-	-	-	-	-	-	●	electric control rear door lock
kinderslot op achterportieren	●	●	●	●	●	●	●	child safety rear door locks
handgrepen vóór en achter	●	●	●	●	●	●	●	front and rear assist grips
kledinghaakjes achter	●	●	●	●	●	●	●	coathanger rear

● = standaard/standard

UITVOERINGSSPECIFICATIES / EQUIPMENT SPECIFICATIONS

INSTRUMENTEN	4-5-deurs / 4-5-door					Wagon		INSTRUMENTS
	L	LX	SLX	SGX	GT	LX	SLX	
analoge quartzklok	●	●	-	-	-	●	-	quartz analogue clock
digitaal quartzklokje	-	-	●	●	●	-	●	quartz digital clock
snelheidsmeter en dagteller	●	●	●	●	●	●	●	speedometer and tripmeter
toerenteller	-	-	●	●	●	-	●	tachometer
brandstofvoorraadmeter	●	●	●	●	●	●	●	fuel level meter
koelvloeistoftemperatuurmeter	●	●	●	●	●	●	●	coolant temperature meter
oliedrukmeter	-	-	-	-	●	-	-	oil pressure meter
regelbare instrumentenverlichting	-	-	●	●	●	-	●	illumination control
indicatie verlichting diverse schakelaars	●	●	●	●	●	●	●	several illuminated switches

VERWARMING / VENTILATIE						HEATING / VENTILATION		
achterruitverwarming	●	●	●	●	●	●	●	electric rear window defroster
airconditioning	-	-	-	●	●	-	-	airconditioning
aanjager met 4 snelheden	●	●	●	●	●	●	●	4-speed blower
druktoetsbediening ventilatiesysteem	●	●	●	●	●	●	●	ventilation system operated by pushbuttons
verwarming naar voertuimte achter	-	-	●	●	●	-	-	rear heater ducts
regel- en richtbare ventilatieroosters	●	●	●	●	●	●	●	adjustable air ventilators
zijruitontwaseming	●	●	●	●	●	●	●	side window defoggers

WAARSCHUWINGS-/ CONTROLELAMPJES						WARNING LAMPS		
groot licht	●	●	●	●	●	●	●	high-beam
mistachterlicht	●	●	●	●	●	●	●	rear fog lamp
brandstofniveau	●	●	●	●	●	●	●	low fuel level
handrem/remvloeistofniveau	●	●	●	●	●	●	●	parking brake/brake fluid level
richtingaanwijzers/alarmlichten	●	●	●	●	●	●	●	direction indicator lamps/hazard warning
laadstroom	●	●	●	●	●	●	●	charge
oliedruk	●	●	●	●	-	●	●	oil pressure
achterruitverwarming	●	●	●	●	●	●	●	rear window defroster
uitgeschakelde overdrive (automaat)	-	●	●	●	-	-	●	overdrive switch off position (automatic)
niet goed gesloten portieren	●	●	●	●	●	●	●	door ajar
ABS remsysteem	-	-	-	-	●	-	-	ABS anti-lock brake system
niveau ruitesproeierreservoir	-	-	●	●	●	-	●	washer fluid
motorcheck (noodloopsysteem) 2.0 benzine	-	●	●	●	●	●	●	engine check (fail safe system) 2.0 petrol
snelgloeisysteem (diesel)	-	●	●	-	-	●	●	quick-glow system (diesel)
water in brandstoffilter (diesel)	-	●	●	-	-	●	●	water-in-fuelfilter (diesel)
geluidssignaal vergeten verlichting	-	●	●	●	●	●	●	headlamp-on reminder
geluidssignaal remblokslijtage vóór	●	●	●	●	●	●	●	audible brake wear sensor

● = standaard/standard

TECHNISCHE GEGEVENS / TECHNICAL SPECIFICATIONS

AFMETINGEN LAADRUIMTE STATIONWAGON	laadlengte max./min.	169/95 cm	cargo length max./min.	DIMENSIONS CARGO SPACE STATIONWAGON
	laadbreedte max./min.	138/113 cm	cargo width max./min.	
	breedte/hoogte geopende achterklep	119/76 cm	width/height tail gate opening	
	max. laadhoogte	83 cm	max. cargo height	
	afstand straat-laadvloer	64 cm	cargo floor height	
	max. stahoogte onder achterklep	190 cm	open rear door height	

TECHNISCHE GEGEVENS / TECHNICAL SPECIFICATIONS

TRANSMISSIE (..) = Wagon	1.6	2.0	2.0 GT	2.0 automaat/ automatic	2.0 diesel	TRANSMISSION (..) = Wagon
overbrengingsverhouding :1						gear ratios :1
1e versnelling	3.333 (←)	3.063 (←)	3.063	2.861 (←)	3.333 (←)	1st gear
2e versnelling	1.955 (←)	1.826 (←)	1.826	1.562 (←)	1.955 (←)	2nd gear
3e versnelling	1.286 (←)	1.207 (←)	1.207	1.000 (←)	1.286 (←)	3rd gear
4e versnelling	0.927 (←)	0.927 (←)	0.927	0.698 (←)	0.927 (0.902)	4th gear
5e versnelling	0.733 (←)	0.733 (0.756)	0.756	-	0.733 (0.756)	5th gear
achteruit	3.417 (←)	3.154 (←)	3.154	2.310 (←)	3.154 (3.417)	reverse
eindreductie	4.056 (←)	4.177 (4.375)	4.177	4.072 (←)	3.895 (4.056)	final drive ratio
aandrijving	Op de voorwielen.		Front.			driving axle
koppeling	Enkelvoudige droge plaatkoppeling met automatische bijstelling, mechanisch bediend. Asbestvrij koppelmateriaal. Automaat: hydraulische koppelomvormer.		Single dry clutch disc with automatic adjuster. Mechanical control. Automatic transmission: hydraulic torque converter. Asbestos free clutch lining materials.			clutch
automatische transmissie	4 versnellingen met automatisch lock-up systeem waarvan de 4e versnelling een elektrisch uitschakelbare overdrive is. Oliekoeler.		4-speed transmission with lock-up and deletable overdrive (fourth gear). Oil-cooler.			automatic transmission

PRESTATIES EN VERBRUIK	Brandstofverbruik volgens Fuel consumption ECE- (liters per 100 km)ECE-norm mode (liters per 100 km)						max. snelheid/ speed km/h		acceleratie/ acceleration 0-100 in sec.		PERFORMANCE AND FUEL CONSUMPTION
	90 km/h		120 km/h		stad/ urban						
	4/5d	Wagon	4/5d	Wagon	4/5d	Wagon	4/5d	Wagon	4/5d	Wagon	
1.6 5-bak	5.3	5.9	6.9	7.8	9.0	9.4	180	170	11.2	13.1	1.6 5-speed
2.0 5-bak	6.0	6.8	7.9	8.8	10.9	11.8	200	190	9.9	10.5	2.0 5-speed
2.0 automaat	6.5	7.2	8.2	9.2	12.1	12.5	190	175	11.5	12.2	2.0 automatic
2.0 GT 5-bak	6.2	-	8.1	-	10.6	-	220	-	8.4	-	2.0 GT 5-speed
2.0 diesel 5-bak	4.5	5.3	6.4	7.3	7.2	7.9	165	155	16.8	17.5	2.0 diesel 5-speed
2.0 diesel automaat	5.2	-	7.3	-	8.1	-	150	-	22.0	-	2.0 diesel automatic

AFMETINGEN / DIMENSIONS GEWICHTEN / WEIGHTS INHOUDEN / CAPACITIES		4-deurs / 4-door				5-deurs / 5-door				Stationwagon		
		1.6	2.0	2.0	2.0	1.6	2.0	2.0	2.0	1.6	2.0	2.0
				GT	diesel			GT	diesel			diesel
lengte / breedte / hoogte length / width / height mm		4400/1700/1390								4460/1695/1470		
wielbasis / wheelbase mm		2550								2550		
spoorbreedte voor/achter / tread fr/rr mm		1470/1460								1460/1460		
massa leeg / kerb weight	5 bak (5-speed) kg	1075	1160	1190	1160	1095	1180	1210	1180	1140	1180	1210
	aut. transm. kg	-	1185	-	1170	-	1205	-	1190	-	1200	-
max. toelaatbare massa permissible total weight	5 bak (5-speed) kg	1570	1665	1685	1620	1590	1685	1705	1620	1780	1810	1845
	aut. transm. kg	-	1690	-	1620	1590	1710	-	1620	-	1840	-
max. massa aanhanger geremd perm. trailing capacity with brake kg		1200	1400		1200	1200	1400		1200	1100	1500	1000
max. massa aanhanger ongeremd perm. trailing capacity without brake kg		500	550		500	500	550		500	500		
max. dakbelasting / max. roof rack weightkg		100										
max. kogeldruk trekhaak max. allowable vertical force on hitchball kg		75										
draaicirkel koetswerk turning circle wall to wall m		11,4	11,7		11,1	11,4	11,7		11,1	11,6		
CW waarde / coefficient of drag CW		0,31		0,29	0,31	0,31		0,29	0,31	0,34		
inhoud brandstoftank / fuel tank capacity ltr		60										
max. inhoud bagageruimte (VDA) capacity luggageroom (VDA) ltr		470				480				1700		

TECHNISCHE GEGEVENS

MOTOR	1.6	2.0	2.0 GT	2.0 diesel
type	Voorin dwarsgeplaatste benzine-/dieselmotor met bovenliggende nokkenas (benzine dubbel, diesel enkel), 4 cilinders in lijn, 5x gelagerde krukas, hydraulische klepstoters (2.0).			
aantal kleppen per cilinder	4	4	4	2
cilinderinhoud cm3	1597	1998	1998	1974
boring x slag mm	76 x 88	86 x 86	86 x 86	84,5 x 88
compressieverhouding: : 1	9,8	9,5	10,0	22,2
max. vermogen kW/pk/min-1	66/90/6000	85/115/6000	110/150/6400	55/75/4800
max. koppel Nm/kgm/min-1	133/13,6/4000	166/16,9/4000	181/18,5/4800	132/13,5/2800
ontsteking	elektronisch			snelgloeisysteem
brandstofsysteem	elektronisch geregelde carbureteur	elektronisch motormanagement systeem (ECCS computer) met zelfdiagnose		roterende brandstof inspuitpomp
		single point injectie	multi point injectie	
brandstofsoort	Euroloodvrij (RON 95)			dieselolie
katalysator	3-weg geregeld met lambda sonde			n.v.t.
accu (onderhoudsvrij)	12 V 60 Ah			12 V 80 Ah
dynamo	12 V 70 A	12 V 80 A	12 V 80 A	12 V 70 A
luchtfilter	droog papierelement			
koeling	vloeistof, gesloten systeem, elektrische ventilator			
	n.v.t.		oliekoeler	

CHASSIS / CARROSSERIE	
wielophanging	Voor: onafhankelijk multi-link (wagon: Mc Pherson) met schroefveren en stabilisator. Achter: onafhankelijk (wagon: torsie-as met Panhardstang) met schroefveren en stabilisator. Hydraulisch-gas gecombineerde schokdempers rondom.
stuurinrichting	Tandheugel. Veiligheidsstuurkolom met stuurslot. Vanaf 1.6 LX stuurbechrachting.
remmen	Hydraulisch, diagonaal gescheiden systeem met bekrachting (GT en wagon tandem-bekrachtiger). Voor: geventileerde schijven; achter: schijven (1.6 + diesel: trommels). Remdrukregelaar (bij 1.6 wagon en 2.0 lastafhankelijk). Anti Blokkeer rem Systeem (ABS) standaard op 2.0 GT. Asbestvrij remvoeringsmateriaal.
banden-velgen	1.6: 165 R 13 op 5JJ x 13; 2.0: 185/65 R 14 op 6JJ x 14; (SGX op lichtmetaal) 2.0 diesel: 185/70 R 13 op 5JJ x 13 (wieldoppen diesel versies als 1.6 LX); 2.0 GT: 195/60 R 14 op 6JJ x 14 (lichtmetaal) Wagon: 1.6/2.0/2.0 diesel: 195/65 R 14 op 5,5 JJ x 14
carrosserie	Zelfdragende carrosserie voorzien van kreukelzones vóór en achter.

SERVICE EN GARANTIE	
Onderhoudsbeurten	Om de 6 maanden afwisselend een inspectie of een onderhoudsbeurt. Indien per jaar méér wordt gereden dan 30.000 km (diesel 20.000 km) om de 15.000 km (diesel 10.000 km) een inspectie en jaarlijks een onderhoudsbeurt. Bij extreme bedrijfsomstandigheden, bijv. veel stationair draaien of zeer hoge jaarkilometrages, is aangepast onderhoud noodzakelijk. Uw dealer kan u hieromtrent adviseren.
Garantie	3 jaar of 100.000 km, al naar gelang het eerste wat zich voordoet. 3 jaar lakgarantie en 6 jaar carrosserie garantie tegen doorroesten van binnenuit, ongeacht het aantal km. Tot max. 3 jaar of 100.000 km garantie op door de Nissan dealer gemonteerde originele onderdelen en accessoires inclusief arbeidsloon. 3 jaar of 100.000 km sleepkosten dekking. 3 jaar of 100.000 km touring assistance in West Europa. 24 uur Nissan Alarm Service in geheel West Europa.



Sommige afbeeldingen kunnen in details verschillen met het in Nederland verkrijgbare model. Nissan Motor Nederland B.V. behoudt zich het recht voor uitrustingsspecificaties, kleuren en prijzen zonder voorafgaande kennisgeving te wijzigen.

TECHNICAL SPECIFICATIONS


ENGINE	1.6	2.0	2.0 GT	2.0 diesel
type	Transversal front mounted gasoline-/diesel engine, with overhead camshaft (petrol double, diesel single), 4 cylinder in line, 5 main bearing crankshaft, hydraulic valve adjusters (2.0).			
valves per cylinder	4	4		2
displacement cm3	1597	1998		1974
bore x stroke mm	76 x 88	86 x 86		84,5 x 88
compression ratio: : 1	9,8	9,5	10,0	22,2
max. power kW/hp/rpm	66/90/6000	85/115/6000	110/150/6400	55/75/4800
max. torque Nm/kgm/rpm	133/13,6/4000	166/16,9/4000	181/18,5/4800	132/13,5/2800
ignition	electronic			quick glow system
fuel system	electronic controlled carburettor	electronic engine (ECCS) management with self diagnosis		diesel injection pump
		single-point fuel injection	multi-point fuel injection	
recommended fuel	unleaded (RON 95)			dieseloil
catalytic converter	3-way system (closed loop)			n.a.
battery (maintenance free)	12 V 60 Ah			12 V 80 Ah
alternator	12 V 70 A	12 V 80 A		12 V 70 A
air filter	dry paper element			
engine cooling	watercooling, closed system, electric cooling fan			
	n.a.		oil-cooler	

CHASSIS AND BODY

suspension	Front: independent multi-link (wagon: Mc Pherson) with coilsprings and stabilizer bar. Rear: independent strut type with coilsprings and parallel links (wagon: trailingarms with torsion beam). Stabilizer bar. Hydraulic gas filled shock absorbers front and rear.
steering type	Rack and pinion. Power assisted steering (not for L version). Energy- absorbing steering column with steering lock.
brakes	Hydraulic diagonal distributed brake system with tandem vacuum brake booster (GT and wagon tandem type). Front: ventilated disc brakes. Rear: disc brakes. (1.6 + diesel: drum brakes) Load sensing valve for rear wheel brake circuit (1.6 wagon and 2.0: dual type). Anti-Lock Braking System (ABS) on GT version. Asbestos free brake lining materials.
wheels and tires	1.6: 165 R 13 on 5JJ x 13 ; 2.0: 185/65 R 14 on 6JJ x 14; (SGX with alloy wheels) 2.0 diesel: 185/70 R 13 on 5JJ x 13 (wheelcovers diesel versions same like 1.6 LX); 2.0 GT: 195/60 R 14 on 6JJ x 14 (alloy wheels). Wagon: 1.6/2.0/2.0 diesel: 195/65 R 14 on 5,5 JJ x 14
body	All steel monocoque body, with safety cabin and deformation zones front and rear.

SERVICE AND WARRANTY


Maintenance intervals	Every 6 months by turns an inspection or major maintenance. If more than 30.000 km (diesel 20.000 km) annually, an inspection every 15.000 km (diesel 10.000 km) and major maintenance once every year. In case of extreme driving conditions, f.i. long periods of idling or high annual mileage, additional maintenance might be required. Your dealer can inform you accordingly.
Warranty	3 years or 100.000 km, whichever comes first. 3 years paint warranty and 6 years perforation from corrosion warranty, regardless of km driven. Till max. 3 years or 100.000 km warranty including labor cost on genuine parts and accessories installed by the Nissan dealer. 3 years or 100.000 km towing cost coverage. 3 years or 100.000 km touring assistance in Western Europe. 24 hours Nissan Emergency Service in Western Europe.



Some pictures might differ in detail from the model available in the Netherlands. Nissan Motor Nederland B.V. reserves all rights to alter at any time without notice prices, colours, materials, equipment specifications of models etc. and to discontinue models or equipment.

Op al onze leveranties en werkzaamheden zijn de Algemene Voorwaarden BOVAG van toepassing welke bij ons, alle Kamers van Koophandel en alle griffies van rechtbanken ter inzage liggen. Op verzoek worden deze u toegezonden.

All of our goods and services are covered by the BOVAG's general conditions (Algemene Voorwaarden BOVAG), these being available for inspection here, at all Chambers of Commerce and at all court registrars' offices in the Netherlands. Copies will be sent on request.



012902